



Manually Operated

THERMOPLASTIC SCREED BOX

Item code: GOSCB

The GO Industrial manual screed box is a tool for applying thermoplastic material to surfaces. It is manually operated, meaning it is pushed or pulled by hand. The screed box is fitted with stability wheels to ensure smooth and even application of the thermoplastic material. It also has a pointer to help guide the user and ensure accurate placement of the material.

SKU	Line Width (mm)	Dimensions (L x W x H mm)	Weight (kg)	Aproximate Container Volume (L)
GOSCB100	100mm	1100 x 180 x 1050	15-20	2.5
GOSCB150	150mm	1100 x 180 x 1050	15-20	3.5
GOSCB200	200mm	1100 x 180 x 1050	15-20	5
GOSCB300	300mm	1100 x 180 x 1050	15-20	7

Thermoplastic road marking material requires precise application at high temperatures (180°C - 210°C). Trained operators must heat the material in thermostatically controlled preheaters, and trained applicators must apply it. Contact LSA for machine/application training. Apply to clean, dry, prepared surfaces for optimal adhesion. Avoid concrete; if necessary, prepare it per the manufacturer's recommendations, including surface treatment and priming.



A: Unit 2 11 to 15 Baylink Avenue,
Deception Bay, QLD, 4508
P: 07 3204 2240
E: sales@goind.com.au
W: www.goind.com.au